

SIMATIC S7-1200, CPU 1217C, compact CPU, DC/DC/DC, 2 PROFINET ports onboard I/O: 10 DI 24 V DC; 4 DI RS-422/485; 6 DO 24 V DC; 0.5 A; 4 DO RS-422/485; 2 AI 0-10 V DC, 2 AO 0-20 mA power supply: DC 20.4-28.8 V DC, program/data memory 250 KB



| General information | |
|--|--|
| Product type designation | CPU 1217C DC/DC/DC |
| Firmware version | V4.6 |
| Engineering with | |
| <ul style="list-style-type: none"> Programming package | STEP 7 V18 or higher |
| Supply voltage | |
| Rated value (DC) | |
| <ul style="list-style-type: none"> 24 V DC | Yes |
| permissible range, lower limit (DC) | 20.4 V |
| permissible range, upper limit (DC) | 28.8 V |
| Reverse polarity protection | Yes |
| Load voltage L+ | |
| <ul style="list-style-type: none"> Rated value (DC) permissible range, lower limit (DC) permissible range, upper limit (DC) | 24 V 20.4 V 28.8 V |
| Input current | |
| Current consumption (rated value) | 600 mA; CPU only |
| Current consumption, max. | 1 600 mA; CPU with all expansion modules |
| Inrush current, max. | 12 A; at 28.8 V DC |
| I^2t | 0.5 A ² s |
| Output current | |
| for backplane bus (5 V DC), max. | 1 600 mA; Max. 5 V DC for SM and CM |
| Encoder supply | |
| 24 V encoder supply | |
| <ul style="list-style-type: none"> 24 V | L+ minus 4 V DC min. |
| Power loss | |
| Power loss, typ. | 12 W |
| Memory | |
| Work memory | |
| <ul style="list-style-type: none"> integrated | 250 kbyte |
| Load memory | |
| <ul style="list-style-type: none"> integrated Plug-in (SIMATIC Memory Card), max. | 4 Mbyte with SIMATIC memory card |
| Backup | |
| <ul style="list-style-type: none"> present maintenance-free without battery | Yes Yes Yes |
| CPU processing times | |
| for bit operations, typ. | 0.08 μs; / instruction |
| for word operations, typ. | 1.7 μs; / instruction |

| | |
|---|---|
| for floating point arithmetic, typ. | 2.3 µs; / Operation |
| CPU-blocks | |
| Number of blocks (total) | DBs, FCs, FBs, counters and timers. The maximum number of addressable blocks ranges from 1 to 65535. There is no restriction, the entire working memory can be used |
| OB | |
| • Number, max. | Limited only by RAM for code |
| Data areas and their retentivity | |
| Retentive data area (incl. timers, counters, flags), max. | 14 kbyte |
| Flag | |
| • Size, max. | 8 kbyte; Size of bit memory address area |
| Local data | |
| • per priority class, max. | 16 kbyte; Priority class 1 (program cycle): 16 KB, priority class 2 to 26: 6 KB |
| Address area | |
| Process image | |
| • Inputs, adjustable | 1 kbyte |
| • Outputs, adjustable | 1 kbyte |
| Hardware configuration | |
| Number of modules per system, max. | 3 comm. modules, 1 signal board, 8 signal modules |
| Time of day | |
| Clock | |
| • Hardware clock (real-time) | Yes |
| • Backup time | 480 h; Typical |
| • Deviation per day, max. | ±60 s/month at 25 °C |
| Digital inputs | |
| Number of digital inputs | 14; Integrated |
| • of which inputs usable for technological functions | 6; HSC (High Speed Counting) |
| Source/sink input | Yes |
| Number of simultaneously controllable inputs | |
| all mounting positions | |
| — up to 40 °C, max. | 14 |
| Input voltage | |
| • Rated value (DC) | 24 V |
| • for signal "0" | 5 V DC at 1 mA |
| • for signal "1" | 15 V DC at 2.5 mA |
| Input delay (for rated value of input voltage) | |
| for standard inputs | |
| — parameterizable | 0.2 ms, 0.4 ms, 0.8 ms, 1.6 ms, 3.2 ms, 6.4 ms and 12.8 ms, selectable in groups of four |
| — at "0" to "1", min. | 0.2 ms |
| — at "0" to "1", max. | 12.8 ms |
| for interrupt inputs | |
| — parameterizable | Yes |
| for technological functions | |
| — parameterizable | Single phase: 3 @ 100 kHz & 3 @ 30 kHz, differential: 3 @ 80 kHz & 3 @ 30 kHz |
| Cable length | |
| • shielded, max. | 500 m; 50 m for technological functions |
| • unshielded, max. | 300 m; for technological functions: No |
| Digital outputs | |
| Number of digital outputs | 10 |
| • of which high-speed outputs | 4; 100 kHz Pulse Train Output |
| Limitation of inductive shutdown voltage to | L+ (-48 V) |
| Switching capacity of the outputs | |
| • with resistive load, max. | 0.5 A |
| • on lamp load, max. | 5 W |
| Output voltage | |
| • for signal "0", max. | 0.1 V; with 10 kOhm load |
| • for signal "1", min. | 20 V |
| Output current | |
| • for signal "1" rated value | 0.5 A |

| | |
|--|--|
| <ul style="list-style-type: none"> • for signal "0" residual current, max. | 0.1 mA |
| Output delay with resistive load | |
| <ul style="list-style-type: none"> • "0" to "1", max. | 1 µs |
| <ul style="list-style-type: none"> • "1" to "0", max. | 5 µs |
| Switching frequency | |
| <ul style="list-style-type: none"> • of the pulse outputs, with resistive load, max. | 100 kHz |
| Relay outputs | |
| <ul style="list-style-type: none"> • Number of relay outputs | 0 |
| Cable length | |
| <ul style="list-style-type: none"> • shielded, max. | 500 m |
| <ul style="list-style-type: none"> • unshielded, max. | 150 m |
| Analog inputs | |
| Number of analog inputs | 2 |
| Input ranges | |
| <ul style="list-style-type: none"> • Voltage | Yes |
| Input ranges (rated values), voltages | |
| <ul style="list-style-type: none"> • 0 to +10 V | Yes |
| <ul style="list-style-type: none"> — Input resistance (0 to 10 V) | ≥100k ohms |
| Cable length | |
| <ul style="list-style-type: none"> • shielded, max. | 100 m; twisted and shielded |
| Analog outputs | |
| Number of analog outputs | 2 |
| Output ranges, current | |
| <ul style="list-style-type: none"> • 0 to 20 mA | Yes |
| Analog value generation for the inputs | |
| Integration and conversion time/resolution per channel | |
| <ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. | 10 bit |
| <ul style="list-style-type: none"> • Integration time, parameterizable | Yes |
| <ul style="list-style-type: none"> • Conversion time (per channel) | 625 µs |
| Analog value generation for the outputs | |
| Integration and conversion time/resolution per channel | |
| <ul style="list-style-type: none"> • Resolution with overrange (bit including sign), max. | 10 bit |
| Encoder | |
| Connectable encoders | |
| <ul style="list-style-type: none"> • 2-wire sensor | Yes |
| 1. Interface | |
| Interface type | PROFINET |
| Isolated | Yes |
| automatic detection of transmission rate | Yes |
| Autonegotiation | Yes |
| Autocrossing | Yes |
| Interface types | |
| <ul style="list-style-type: none"> • RJ 45 (Ethernet) | Yes |
| <ul style="list-style-type: none"> • Number of ports | 2 |
| <ul style="list-style-type: none"> • integrated switch | Yes |
| Protocols | |
| <ul style="list-style-type: none"> • PROFINET IO Controller | Yes |
| <ul style="list-style-type: none"> • PROFINET IO Device | Yes |
| <ul style="list-style-type: none"> • SIMATIC communication | Yes |
| <ul style="list-style-type: none"> • Open IE communication | Yes; Optionally also encrypted |
| <ul style="list-style-type: none"> • Web server | Yes |
| <ul style="list-style-type: none"> • Media redundancy | Yes |
| PROFINET IO Controller | |
| <ul style="list-style-type: none"> • Transmission rate, max. | 100 Mbit/s |
| Services | |
| <ul style="list-style-type: none"> — PG/OP communication | Yes; encryption with TLS V1.3 pre-selected |
| <ul style="list-style-type: none"> — Isochronous mode | No |
| <ul style="list-style-type: none"> — IRT | No |
| <ul style="list-style-type: none"> — PROFIenergy | No |
| <ul style="list-style-type: none"> — Prioritized startup | Yes |

| | |
|---|---|
| — Number of IO devices with prioritized startup, max. | 16 |
| — Number of connectable IO Devices, max. | 16 |
| — Number of connectable IO Devices for RT, max. | 16 |
| — of which in line, max. | 16 |
| — Activation/deactivation of IO Devices | Yes |
| — Number of IO Devices that can be simultaneously activated/deactivated, max. | 8 |
| — Updating time | The minimum value of the update time also depends on the communication component set for PROFINET IO, on the number of IO devices and the quantity of configured user data. |

PROFINET IO Device

Services

| | |
|---|--|
| — PG/OP communication | Yes; encryption with TLS V1.3 pre-selected |
| — Isochronous mode | No |
| — IRT | No |
| — PROFIenergy | Yes |
| — Shared device | Yes |
| — Number of IO Controllers with shared device, max. | 2 |

Protocols

| | |
|-----------------------------------|---|
| Supports protocol for PROFINET IO | Yes |
| PROFIsafe | No |
| PROFIBUS | Yes; CM 1243-5 (master) or CM 1242-5 (slave) required |
| OPC UA | Yes; OPC UA Server |
| AS-Interface | Yes; CM 1243-2 required |

Protocols (Ethernet)

| | |
|----------|-----|
| • TCP/IP | Yes |
| • DHCP | No |
| • SNMP | Yes |
| • DCP | Yes |
| • LLDP | Yes |

Redundancy mode

Media redundancy

| | |
|--------|--|
| — MRP | Yes; as MRP redundancy manager and/or MRP client |
| — MRPD | No |

SIMATIC communication

| | |
|--------------|-----|
| • S7 routing | Yes |
|--------------|-----|

Open IE communication

| | |
|------------------------|------------|
| • TCP/IP | Yes |
| — Data length, max. | 8 kbyte |
| • ISO-on-TCP (RFC1006) | Yes |
| — Data length, max. | 8 kbyte |
| • UDP | Yes |
| — Data length, max. | 1 472 byte |

Web server

| | |
|-------------------------|-----|
| • supported | Yes |
| • User-defined websites | Yes |

OPC UA

| | |
|--|--|
| • Runtime license required | Yes; "Basic" license required |
| • OPC UA Server | Yes; data access (read, write, subscribe), method call, runtime license required |
| — Application authentication | Available security policies: None, Basic128Rsa15, Basic256Rsa15, Basic256Sha256 |
| — User authentication | "anonymous" or by user name & password |
| — Number of sessions, max. | 10 |
| — Number of subscriptions per session, max. | 5 |
| — Sampling interval, min. | 100 ms |
| — Publishing interval, min. | 200 ms |
| — Number of server methods, max. | 20 |
| — Number of monitored items, recommended max. | 1 000 |
| — Number of server interfaces, max. | 2 |
| — Number of nodes for user-defined server interfaces, max. | 2 000 |

Further protocols

| | |
|---|--|
| • MODBUS | Yes |
| communication functions / header | |
| S7 communication | |
| • supported | Yes |
| • as server | Yes |
| • as client | Yes |
| • User data per job, max. | See online help (S7 communication, user data size) |
| Number of connections | |
| • overall | PG Connections: 4 reserved / 4 max; HMI Connections: 12 reserved / 18 max; S7 Connections: 8 reserved / 14 max; Open User Connections: 8 reserved / 14 max; Web Connections: 2 reserved / 30 max; OPC UA Connections: 0 reserved / 10 max; Total Connections: 34 reserved / 64 max |
| Test commissioning functions | |
| Status/control | |
| • Status/control variable | Yes |
| • Variables | Inputs/outputs, memory bits, DBs, distributed I/Os, timers, counters |
| Forcing | |
| • Forcing | Yes |
| Diagnostic buffer | |
| • present | Yes |
| Traces | |
| • Number of configurable Traces | 2 |
| • Memory size per trace, max. | 512 kbyte |
| Interrupts/diagnostics/status information | |
| Diagnostics indication LED | |
| • RUN/STOP LED | Yes |
| • ERROR LED | Yes |
| • MAINT LED | Yes |
| Integrated Functions | |
| Frequency measurement | Yes |
| controlled positioning | Yes |
| Number of position-controlled positioning axes, max. | 8 |
| Number of positioning axes via pulse-direction interface | 4; With integrated outputs |
| PID controller | Yes |
| Number of alarm inputs | 4 |
| Number of pulse outputs | 4 |
| Limit frequency (pulse) | 1 MHz |
| Potential separation | |
| Potential separation digital inputs | |
| • Potential separation digital inputs | No |
| • between the channels, in groups of | 1 |
| Potential separation digital outputs | |
| • Potential separation digital outputs | Yes |
| • between the channels | No |
| • between the channels, in groups of | 1 |
| EMC | |
| Interference immunity against discharge of static electricity | |
| • Interference immunity against discharge of static electricity acc. to IEC 61000-4-2 | Yes |
| — Test voltage at air discharge | 8 kV |
| — Test voltage at contact discharge | 6 kV |
| Interference immunity to cable-borne interference | |
| • Interference immunity on supply lines acc. to IEC 61000-4-4 | Yes |
| • Interference immunity on signal cables acc. to IEC 61000-4-4 | Yes |
| Interference immunity against voltage surge | |
| • Interference immunity on supply lines acc. to IEC 61000-4-5 | Yes |
| Interference immunity against conducted variable disturbance induced by high-frequency fields | |
| • Interference immunity against high-frequency radiation acc. to IEC 61000-4-6 | Yes |
| Emission of radio interference acc. to EN 55 011 | |

- Limit class A, for use in industrial areas
- Limit class B, for use in residential areas

Yes; Group 1

Yes; When appropriate measures are used to ensure compliance with the limits for Class B according to EN 55011

Degree and class of protection

IP degree of protection IP20

Standards, approvals, certificates

| | |
|-----------------------|-----|
| CE mark | Yes |
| UL approval | Yes |
| cULus | Yes |
| FM approval | Yes |
| RCM (formerly C-TICK) | Yes |
| KC approval | Yes |
| Marine approval | Yes |

Ambient conditions

Free fall

- Fall height, max. 0.3 m; five times, in product package

Ambient temperature during operation

- min. -20 °C
- max. 60 °C; Number of simultaneously activated inputs or outputs 7 or 5 (no adjacent points) at 60 °C horizontal or 50 °C vertical, 14 or 10 at 55 °C horizontal or 45 °C vertical
- horizontal installation, min. -20 °C
- horizontal installation, max. 60 °C
- vertical installation, min. -20 °C
- vertical installation, max. 50 °C

Ambient temperature during storage/transportation

- min. -40 °C
- max. 70 °C

Air pressure acc. to IEC 60068-2-13

- Operation, min. 795 hPa
- Operation, max. 1 080 hPa
- Storage/transport, min. 660 hPa
- Storage/transport, max. 1 080 hPa

Altitude during operation relating to sea level

- Installation altitude, min. -1 000 m
- Installation altitude, max. 5 000 m; Restrictions for installation altitudes > 2 000 m, see manual

Relative humidity

- Operation, max. 95 %; no condensation

Vibrations

- Vibration resistance during operation acc. to IEC 60068-2-6 2 g (m/s²) wall mounting, 1 g (m/s²) DIN rail
- Operation, tested according to IEC 60068-2-6 Yes

Shock testing

- tested according to IEC 60068-2-27 Yes; IEC 68, Part 2-27 half-sine: strength of the shock 15 g (peak value), duration 11 ms

Pollutant concentrations

- SO₂ at RH < 60% without condensation SO₂: < 0.5 ppm; H₂S: < 0.1 ppm; RH < 60% condensation-free

configuration / header

configuration / programming / header

| | |
|----------------------|-----|
| Programming language | |
| — LAD | Yes |
| — FBD | Yes |
| — SCL | Yes |

Know-how protection

- User program protection/password protection Yes
- Copy protection Yes
- Block protection Yes

Access protection

- protection of confidential configuration data Yes
- Protection level: Write protection Yes
- Protection level: Read/write protection Yes
- Protection level: Complete protection Yes

programming / cycle time monitoring / header

- adjustable

Yes

Dimensions

| | |
|--------|--------|
| Width | 150 mm |
| Height | 100 mm |
| Depth | 75 mm |

Weights

| | |
|-----------------|-------|
| Weight, approx. | 530 g |
|-----------------|-------|

last modified:

3/12/2024 